



Hydronic High Wall Air Conditioners



Product 05-25

- Modern and compact design
- Wide angle air distribution
- Air filter
- Air sweep auto swing
- Low noise level
- Three way valve(option)



HH25



HH05-14

Controller

- Wireless remote version available I-5008
- 5 Operation modes
(Cool/Heat/Auto/Dry/Fan)
- Room temperature setting
- Fan speed selection
- LED display



Specification: Hydronic High Wall 50/60Hz Rev.00

Models		Indoor	HHH-C						
		Unit	05	07	11	14	25		
Nominal Capacities	Cooling	Btu/h	5,391	7,472	11,771	13,443	24,000		
		kW	1.58	2.19	3.45	3.94	7.03		
		kcal/h	1,358	1,882	2,965	3,387	6,046		
	Heating	Btu/h	7,677	9,997	16,480	18,834	24,700		
		Kw	2.25	2.93	4.83	5.52	7.24		
		kcal/h	1,934	2,518	4,152	4,745	6,222		
Power Supply		V/Ph/Hz	220-240/1/50 or 208-230/1/60						
		Ph	1						
Power Consumption		W	21/22	30/24	29/32	50/52	84/91		
Running Current		A	0.10/0.09	0.13/0.11	.15/.17	.2/.24	.39/.42		
Indoor Unit	Power Supply		V/Ph/Hz	220-240/1/50 or 208-230/1/60					
			Ph	1					
	Fan	Fan Type		Tangential/Direct Drive					
		Air flow		m ³ /h	300	390	535	730	1120
		Input Power		W	21/22	30/24	29/32	50/52	84/91
		Running Current		A	0.10/0.09	0.13/0.11	0.15/0.17	0.2/0.24	0.39/0.42
		Fan Motor Protection		Auto Restart Thermal Overload Protector					
	Coil	Tube	Material	Smooth Tube					
			Diameter	Ø7					
		Fin	Material	Aluminium					
			Row	2	2	2	2	2	
			Fin per inch	19	21	21	19	18	
		Face Area		m ²	0.141	0.141	0.151	0.205	0.329
	Dimension	Height		mm	290	290	315	315	325
		Width		mm	799	799	1019	1019	1095
		Depth		mm	181	181	190	190	230
	Packing Dimension	Height		mm	350	350	380	380	385
		Width		mm	840	840	1094	1094	1170
		Depth		mm	230	230	260	260	290
	Net Weight		kg	8	8	13	13	18	
	Gross Weight		kg	9	9	14	14	19.5	
	System Operation Control		Wireless Control with LCD Display						
	Condensate Drainage(I.D.)		mm	12	12	16.5	19.05	16.5	
	Air Filter		Polypropylene						
	Water connection	Type		Thread Male Connection					
		Diameter		inch	1/2	1/2	1/2	1/2	1/2

Remark: The above design and specification are subject to change without prior notice for product improvement.

Asia Headquarters
 20/F, Tower 1, 2 & 3, Enterprise Square 1,
 9 Sheung Yuet Road, Kowloon Bay, Kowloon,
 Hong Kong
 Tel : +852 2590 0012
 Fax: +852 2516 5648

